



Retractable Tool Lanyard Easy Reel (Fixed Belt Loop)

The Easy Reel Fixed Belt Loop is a recommended tool accessory for the Cobra MKII, suited to professionals across all industrial applications with intense tool handling operations. The fixed loop arrangement is the most common and straight forward tool belt fastening method. The belt loop simply slides onto your existing belt strap to provide a secure attachment for the Easy Reel system. The Easy Reel provides Omni-directional rotation through 360 degrees on both X and Y axis. This means the reel follows the direction of tool movement, insuring the cable pull-out is always in-line with the bottom of the housing (cable exit bush) resulting in:

- Reduced reel wear - Extended reel life - Lower reel drag (minimising repetitive strain)*
- Lessen operator fatigue increasing productivity -*
- Minimised karabiner minor axis rollout failure - Stops twisting for quicker tool pick-up*

FEATURES

The fixed belt loop design provides a structurally secure fitting method between your existing tool belt and the Easy Reel system. Your belt is simply threading directly through the fixed belt loop slot. (Maximum Belt width 50mm)

The Easy Reel ensures the Cobra's connector (karabiner) always has major axis alignment regardless of scope of use or harness and belt angle configuration. Preventing system failure through connector minor axis rollout (gate opening) in dynamic loading i.e. when tool is dropped.

By effectively having two in-line swivels (Easy Reel + Cobra) eliminates any chance of cable twisting or snagging caused from intense tool turning movement, combined with the reel housing always following tool movement ensuring constant direct alignment improves cable loading onto the drum, which collectively provides smoother reel action with faster cable retraction time after time.

An additional benefit of the Easy Reel Fixed Belt Loop is having a constant tool alignment. Reducing general component wear (less friction), therefore extending the service life of the Cobra MKII reel in the field. And because there is less friction it means lower drag, making it freer to pull the cable out of the reel. Intense tool handling operation becomes lighter, lessening the fatigue therefore improving productivity performance.

Overall maximum safe working load of 5kgs
(Dynamically tested - see 'testing pages' for more info)

Manufactured using premium industrial webbing and bar tacked at both ends for superior strength structurally, incorporating a stainless steel swivel link

Individually serialised for clear easy inspection, full traceability and control

Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Total length: 23cm / Width: 6cm / Weight: 0.04kgs

Manufactured at our product factory in the UK



Code	Name	Description
EASYRBELTL	Fixed Belt Loop (only)	Supplied with (Plain) no connectors
EASYRBELTLCOBRA	Fixed Belt Loop + Cobra MKII	Supplied with (Plain) no connectors
EASYRBELTLCOBRA-K	Fixed Belt Loop + Cobra MKII	Supplied with 1 x Karabiner
EASYRBELTLCOBRA-M	Fixed Belt Loop + Cobra MKII	Supplied with 1 x Mallion
EASYRBELTLCOBRA-SSG	Fixed Belt Loop + Cobra MKII	1 x Large Stainless Screw Gate Karabiner

