



Tool Bags - PRO MEWP Bag (PVC)

The PRO MEWP Bag is the ultimate tailored storage and tool tethering solution for technicians working on plant. The design allows complete flexibility in fitting options to suit all access equipment configurations, allowing the tool bag to be directly attached to either the rails or tubing of the plant, towers or powered access platform. The reinforcement used throughout the bag is optimised structurally to prevent crushing and closure when the bag is fully loaded, providing a wide clear opening for easy quick access. Extra features include a mesh base which allows natural illumination for better internal visibility and ventilation, and a bag roll-back lid system for ease of access and entry into the bag.

FEATURES

Central dividers form three main internal compartments, with five additional large front pockets. The bag rigidity is achieved using five internal closed-cell reinforcement marine battens. A securing system is fixed to the bag bottom facilitating attachment to the toe rail of basket / MEWP platform etc (Bag capacity 80kgs)

A choice of four securing arrangements method: Belt Loop / Eyelets / Triple Action Velcro Straps / Triple Action Safety Buckle (see 'Tool Bag & Holster Fixing Options' page)

The bag has a buckle to hold down the lid and secure the contents during transportation or MEWP movement. The lid features a roll-back system allowing it to be secured out of the way whilst the bag is in use

The bag is manufactured from defence specification, high grade polyester that is UV stabilised and mildew resistant, providing superior strength and wear characteristics, with all structural parts triple sewn. Only premium industrial grade components are used, and finished with 'soft edged' binding for wear reinforcement

Structural mesh base allows natural illumination for better internal visibility and ventilation, being made up of a double layer sandwich of structural mesh and clear acrylic, which provides superior strength and wear characteristics, and incorporating eyelet drainage holes. (Structural mesh is synthetic woven multi-braid fabric encapsulated in a plastic coating)

6 x internal and 10 x external structural 'D' ring anchorage points individually rated up to 5kgs (Dynamically tested - see 'testing pages' for more info). Rated using a 2:1 safety factor

Individually serialised for clear easy inspection, full traceability and control

Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Height: 35cm / Depth: 17cm / Width: 45cm / Volume: 20L / Weight: 1.25kgs

Manufactured at our height safety product factory in the UK



Code	Model	Description
PROMEWPBAGL	Loop Fastening	Slides onto standard belts up to 50mm wide
PROMEWPBAGE	3x Eyelet Fastening	Hung from belt/gear loops using a connector
PROMEWPBAGV	3x Velcro Fastening	Wraps around fixing point with triple lock action
PROMEWPBAGB	3x Buckle Fastening	Secures around fixing point triple lock action