



FEATURES

Advanced Linesmen's bag fitting system (option). Specially developed to allow maximum bag positioning choice. The engineer can place the bag anywhere on his harness belt i.e. directly onto the webbing belt strap or back pad etc.

The lid hinge is uniquely reorganised to open and close from the outside front edge of the bags main compartment (just above the front pocket) creating a shorter arrangement reducing bulk, improving internal content and tethering visibility, and reducing climbing constraints by the repositioning the lid and thus aiding rotational mobility and flexibility.

The lid additionally features a roll-back system allowing it to be secured out of the way providing clear unobstructed access, which can be closed during transportation or climbing to prevent spillage of contents.

The base and sides of the bag have Polycarbonate clear panels aiding perimeter rigidity and load distribution and tool impact, whilst allowing tool holster support and tool insertion alignment.

3 x internal and 2 x external structural 'D' ring anchorage points individually rated up to 5kgs (Dynamically tested - see 'testing pages' for more info)

Designed to carry tools in the main reinforced compartment, with an additional large front external pocket, both sides also have a combination tool holster. The holsters are developed to accommodate pliers, ratchets and podger making them versatile to suit line's engineers specific tool arrangement

A choice of five securing arrangements method: Belt Loop/ Eyelets/ Triple Action Velcro Straps/ STD Triple Action Safety Buckle and Advanced Linesmen's System (see 'Tool Bag & Holster Fixing Options' page)

The bag shape and finish is ergonomically optimised for load efficiency & wearing comfort

Individually serialised for clear easy inspection, full traceability and control Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Height: 43cm / Depth: 9cm / Width: 23cm / Volume: 7L / Weight: 0.94kgs

Manufactured at our height safety product factory in the UK

Tool Bags Linesmans Tool Bag PVC MKII

The Linesman's (PVC) MKII tool bag was conceived specifically for arduous conditions, above and beyond normal harsh field applications, whilst carrying securely tethered tools at height. Exclusively developed for line's engineers, with National Grid over an extensive six month period of continuous field trials, prototypes, review meetings etc. The bag design features technically superior reinforcement, including the use of Polycarbonate clear panels in the side and base. The body is made from dual layers of heavy duty PVC, optimised further with structural sewing and corner protection make the bag virtually indestructible.



Code	Model	Description
LTBPVCMKIIL	Loop Fastening	Slides onto standard belts up to 50mm wide
LTBPVCMKIIE	2x Eyelet Fastening	Hung from belt/gear loops using a connector
LTBPVCMKIIV	2x Velcro Fastening	Wraps around fixing point with triple lock action
LTBPVCMKIIB	2x Buckle Fastening	Secures around fixing point with triple lock action
LTBPVCMKIIP	2x Linesmen System	Advanced Positioning System with triple lock action



Advanced Linesmen's bag fitting system (secured around back-pad)



Advanced Linesmen's bag fitting system (secured around webbing belt strap)





FEATURES

The lid hinge is uniquely reorganised to open and close from the outside front edge of the bags main compartment (just above the front pocket) creating a shorter configuration reducing bulk, improving internal content and tethering visibility, and reducing climbing constraints by the repositioning the lid and thus aiding rotational mobility and flexibility.

The lid additionally features a roll-back system allowing it to be secured out of the way providing clear unobstructed access, which can be closed during transportation or climbing to prevent spillage of contents.

The base and sides of the bag have Polycarbonate clear panels aiding perimeter rigidity, whilst allowing Tool Frog support and tool insertion alignment.

The whole bag is made using two layers of structural mesh (synthetic woven multi-braid fabric encapsulated in a plastic coating), ensuring optimum strength and performance wear characteristics (virtually indestructible)

3 x internal and 4 x external structural 'D' ring anchorage points individually rated up to 5kgs (Dynamically tested - see 'testing pages' for more info).
Rated using a 2:1 safety factor

Designed to carry tools and components in the main reinforced compartment, with an additional large front external pocket, complete with 2x sets of double tool frogs mounted on the sides

A choice of five securing arrangements method: Belt Loop/ Eyelets/ Triple Action Velcro Straps/ STD Triple Action Safety Buckle and Advanced Linesmen's System (see 'Tool Bag & Holster Fixing Options' page)

The bag shape and finish is ergonomically optimised for load efficiency and wearing comfort

Individually serialised for clear easy inspection, full traceability and control

Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Height: 44cm / Depth: 10cm / Width: 23cm / Volume: 7L / Weight: 0.66kgs

Tool Bags Alliance (Medium Bag 2) Mesh

The Alliance (Medium Bag 2) mesh tool bag is a specialist Linesman's tool bag, developed in conjunction with Babcock for the Energy Alliance. The Alliance bag has been uniquely configured to overcome the harsh product demands from daily use in the field by network engineers. The bag design features sophisticated reinforcement, including the use of Polycarbonate clear end panels in the side and base, double wall complete structural mesh body (synthetic woven multi-braid fabric encapsulated in a plastic coating) optimised further with increased structural sewing make the bag virtually indestructible. The advanced bag properties make it super lightweight, with the mesh allowing natural illumination for better internal visibility and ventilation, thereby assisting the user in contents identification and tool selection, with the added benefits of air circulation through the bag.



Code	Model	Description
TBAB2ML	Loop Fastening	Slides onto standard belts up to 50mm wide
TBAB2ME	2x Eyelet Fastening	Hung from belt/gear loops using a connector
TBAB2MV	2x Velcro Fastening	Wraps around fixing point with triple lock action
TBAB2MB	2x Buckle Fastening	Secures around fixing point with triple lock action
TBAB2MAP	2x Linesmen System	Advanced Positioning System with triple lock action