



FEATURES

A choice of four securing methods is available: The fixing arrangements include either: Belt Loop / Eyelets / Triple Action Velcro Straps / Triple Action Safety Buckle (see 'Tool Bag & Holster Fixing Options' page)

The bag provides four structural 'D' ring anchorage points each rated up to 5kgs (Dynamically tested - see 'testing pages' for more info). Rating uses a 2:1 safety factor

Designed to carry tools and parts up to 20kgs in the main compartment, with a mesh side and front pockets, c/w drain hole

Ergonomically optimized for user comfort and weight distribution, with a top opening and bag depth configured to limit accidental spillage

Built to withstand the rigors of extreme military, utility and construction environments being manufactured from defence high grade polyester (UV stabilised and mildew resistance) fabric outer shell, structural marine mesh, premium industrial webbing, aluminium buckles, soft 'edged' for wear and reinforcement

Individually serialised for clear easy inspection, full traceability and control

Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Height: 24cm / Depth: 9cm / Width: 27cm / Volume: 6L / Weight: 0.30kgs

Manufactured at our product factory in the UK

Manufactured at our height safety product factory in the UK

Tool Bags - Medium Bag (PVC)

Leading Edge has created the advanced medium tool bag. Constructed in defence grade materials and also ergonomically created with regard to load efficiency. Produced for any trade specialist where they are required to transport and tether small tools and items at height. Having structural anchorage points each one rated to 5kgs. Connection on your harness/belt can be by means of a choice of end user determined attachment alternatives.



Code	Model	Description
TBAGPVCML	Loop Fastening	Slides onto standard belts up to 50mm wide
TBAGPVCME	2x Eyelet Fastening	Hung from belt/gear loops using a connector
TBAGPVCMV	2x Velcro Fastening	Wraps around fixing point with triple lock action
TBAGPVCMB	2x Buckle Fastening	Secures around fixing point with triple lock action