



Tool Belts Pro-Anchor (Velcro)

The Pro-Anchor (Velcro) fastening system provides maximum anchorage flexibility and directional load security. The design allows the strap to be easily repositioned, and combined with the unique unidirectional geometry provides high shear performance. The Pro-Anchor (Velcro) allows fitting to harness straps, tool belt, handrails or plant (Maximum 50mm diameter). The system consists of three Velcro and webbing 50mm wide straps, which overlap each other in opposing directions increasing the tensile strength of the fastening. The Pro-Anchor (Velcro) is structurally rated to 10kgs (dynamically test to 20kgs) rated using a 2:1 safety factor. The wrapping style securing method will accommodate captive (pre-terminated, i.e. where you cannot slide on a loop) existing tool belt and harness straps, MEWP handrail or Scaffold tube configurations.

FEATURES

The unique design makes this configuration one of the most versatile of all retro-fitting tether fastening arrangements being suitable for harness straps, belts, scaffolding and MEWP/ Scissor lift handrails, plant etc

Advanced Velcro design features a triple over-lock system, which consists of three Velcro and webbing straps, which overlap each other in opposing directions increasing the tensile strength of the fastening, combined with the unique unidirectional geometry providing high shear performance.

Overall maximum safe working load of 10kgs (Dynamically tested - see 'testing pages' for more info). Rated using a 2:1 safety factor with either a single (10kgs) or double 'D' ring configuration (5kgs each)

Manufactured from high quality 50mm wide industrial webbing, and structurally sewn for wear reinforcement and strength

Individually serialised for clear easy inspection, full traceability and control

Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Height: 9cm / Width: 5cm / Weight: 0.02kgs

Manufactured at our product factory in the UK



Code	Style	Description
PROANCVELD	Single D Ring	(Plain) No Connectors
PROANCVELDK	Single D Ring	Supplied with Karabiner x1
PROANCVELDM	Single D Ring	Supplied with Mallion x1
PROANCVELDD	Double D Rings	(Plain) No Connectors
PROANCVELDDK	Double D Rings	Supplied with Karabiner x2
PROANCVELDDM	Double D Rings	Supplied with Mallion x2