



### Wrist Tool Lanyard (PRO WIRE LOOP) Velcro Fastening

The (Pro Wire Loop) Velcro fastening wrist tool lanyard is manufactured by Leading Edge in the UK. The construction has been optimised designed for toughness in harsh as well as abrasive conditions, where synthetic cords wouldn't be appropriate. The actual loop is manufactured making use of 2mm stainless-steel wire encapsulated inside a protective rubber sleeve. Working with a wrist tool lanyard allows quick tool pick-up, ideally suitable for single tool repeated use, i.e. technicians and trades doing work at height where it can help having the tool readily available for ease of use and increased productivity, as well as combined with exceptional tool connection flexibility i.e. looping, choking or use with a connector. The wrist tool lanyard features a special product design which simply requires the use of one hand to fit and adjust. All Leading Edge wrist lanyards possess a unique safety release expansion joint, protecting against de-gloving in an accident. This innovation enables the wrist strap to come free in an emergency, releasing the hand from getting drawn into possible danger should their tool/lanyard end up getting trapped, for instance in rotating equipment. The expansion joint comes in two options i.e. full expansion and a half expansion joint.

#### FEATURES

This wrist lanyard is fitted having a extremely secure rated Velcro fastening system, enabling quicker adjustment and is also simpler to put-on and take-off when working with multiple pre-tethered tools

The wrist tool lanyards can be purchased in a choice of two safety release expansion joint configuration settings to accommodate both application and danger of exposure to de-gloving in an accident

The expansion joint additionally gives added user wearing comfort as well as flexibility

The (Full) expansion joint option is an 8cm link that expands to 17cms (112% stretch) suitable for tools up to 2kgs and where this is a risk of lanyard being caught in rotating machinery. The full expansion joint allows the hand to be pulled free very quickly

The (Half) expansion joint option is a 5cm link that expands to 9cms (80% stretch) suitable for tools up to 5kgs allows hand to be pulled free should the lanyard become trapped (not for use with rotating machinery which may require a faster release). The half expansion joint has better wear characteristics

Supplied with a stainless steel wire (encapsulated in a protective rubber sleeve) loop and toggle, which allows direct tool attachment via choking, looping or use with a connector

Individually serialised for clear easy inspection, full traceability and control

Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Rated for hand tools up to 5kgs (Dynamically tested - see 'testing pages' for more info). Rating using a 2:1 safety factor

The wrist lanyard is made from premium polyester webbing, industrial grade elastic tape, and 3mm multi-braid rope, and marine grade premium adjustable buckle, finished to a high standard. Lanyard weight: 0.01kgs (without connectors)

Manufactured at our height safety product factory in the UK



Code	Expansion Joint	Description
WTLPLVFULLK	Full Expansion	Supplied with Karabiner
WTLPLVFULLM	Full Expansion	Supplied with Mallion
WTLPLVFULLP	Full Expansion	Supplied with (Plain) No Connectors
WTLPLVHALFK	Half Expansion	Supplied with Karabiner
WTLPLVHALFM	Half Expansion	Supplied with Mallion
WTLPLVHALFP	Half Expansion	Supplied with (Plain) No Connectors