



FEATURES

This lanyard is fitted with a premium adjustable buckle configuration which provides ease of adjustment for both tightening and releasing. The design is compact, hard wearing and has a long life in arduous environments

The wrist tool lanyards are available in a choice of two safety release expansion joint configurations to suit both application and risk of exposure to de-gloving in an accident. The expansion joint also provides additional user wearing comfort and flexibility

The (Full) expansion joint option is an 8cm link that expands to 17cms (112% stretch) suitable for tools up to 2kgs and where this is a risk of lanyard being caught in rotating machinery. The full expansion joint allows the hand to be pulled free very quickly

The (Half) expansion joint option is a 5cm link that expands to 9cms (80% stretch) suitable for tools up to 5kgs allows hand to be pulled free should the lanyard become trapped (not for use with rotating machinery which may require a faster release). The half expansion joint has better wear characteristics

Elasticated design reduces tripping, snagging hazards and lowers impact force on the wrist from dropped tool loading. Twin elastic tapes are used inside every lanyard for improved operational performance and durability, and incorporate an in-line swivel to prevent lanyard twisting when rotating tools

Wrist lanyard lengths: 30cm and 60cm. Stretch: 30cm expands to 40cm, 60cm to 90cm

Rated for hand tools up to 5kgs (Dynamically tested - see 'testing pages' for more info). Rated using a 2:1 safety factor. Lanyard weight: 0.06kgs (without connectors)

Individually serialised for clear easy inspection, full traceability and control

Issued with a 'Declaration of Conformity' product certificate and 'Final Inspection' sheet

Electrical Conductivity and Resistivity Test*: Dry >200 Giga-ohms / Wet >4 Mega-ohms
*Wiring regulations (BS7671). Live working hand tools (EN 60900)

Made using premium polyester webbing, industrial grade elastic tape, a stainless steel swivel, and marine grade premium adjustable buckle, finished to a high standard

Twin elastic tapes are used inside every lanyard for improved operational performance and durability. Manufactured at our height safety product factory in the UK

Wrist Tool Lanyard (Swivel & Elastic) Buckle Fastening

The (Swivel & Elastic) wrist tool lanyard is made in the UK by Leading Edge. The design pulls together the user advantages of using a wrist lanyard i.e. easy tool pick-up, ideally suited for single tool repetitive use, as well as users working at height where it is essential to prevent dropped tools and where it helps to have the tool accessible for speed and efficiency. Whilst combining the benefits of an elasticated lanyard in reducing tripping, snagging hazards and lowers impact force on the wrist from a dropped tool. This wrist lanyard incorporates a swivel into the system preventing the lanyard from twisting when rotating the tool in applications such as scaffolding, where the user is turning the tool continually i.e. a podger, ratchet etc., therefore reducing entanglement and preventing connector failure from miss-loading the minor axis. All Leading Edge wrist lanyards have a unique safety release expansion joint, preventing de-gloving in an accident. The design makes it possible for the wrist strap to come free in an emergency releasing the hand from becoming drawn into potential hazards should their tool/lanyard become caught-up, as for example in rotating machinery. The expansion joint is available in two options i.e. full expansion and a half expansion joint.



Code	Length	Expansion Joint	Description
WTLSEBFULLK3	Small (300mm)	Full Expansion	Supplied with Karabiner
WTLSEBFULLK6	Medium (600mm)	Full Expansion	Supplied with Karabiner
WTLSEBFULLM3	Small (300mm)	Full Expansion	Supplied with Mallion
WTLSEBFULLM6	Medium (600mm)	Full Expansion	Supplied with Mallion
WTLSEBFULLP3	Small (300mm)	Full Expansion	Supplied with (Plain) No Connector
WTLSEBFULLP6	Medium (600mm)	Full Expansion	Supplied with (Plain) No Connector
WTLSEBHALFK3	Small (300mm)	Half Expansion	Supplied with Karabiner
WTLSEBHALFK6	Medium (600mm)	Half Expansion	Supplied with Karabiner
WTLSEBHALFM3	Small (300mm)	Half Expansion	Supplied with Mallion
WTLSEBHALFM6	Medium (600mm)	Half Expansion	Supplied with Mallion
WTLSEBHALFP3	Small (300mm)	Half Expansion	Supplied with (Plain) No Connector
WTLSEBHALFP6	Medium (600mm)	Half Expansion	Supplied with (Plain) No Connector